Lessons For Extracting Energy From Landfill Waste from experience in the wood processing industry

Brian Cox
East Harbour Management Services

Presentation to WasteMINZ Bioenergy Workshop, Napier 27 May 2003

Drivers for Electricity Generation

- Post Maui opportunities
 - multiple gas supplies
- Integrated energy solutions
 - Paradigm shifts in thinking about energy
- Distributed generation
 - reliability and security of supply
 - reduction in electricity network connection costs
- Requirements for heat
 - cogeneration
 - waste disposal costs
- High spot market prices




Drivers for Heat

- Demand for heat in wood processing
- Cogeneration
- Cost effective now
- Disposal of waste
- Environmentally sound disposal option




Cost of Heat




East Harbour

Future Heat Costs (post 2007)



Future Electricity Cost (post 2007)



Barriers to Generation from Landfill Waste

- Waste is usually contaminated
- Waste is not homogenous
- Labour intensive processing into a fuel
- Needs to be transported to combustor
- Needs a heat customer (cogeneration) or to be embedded generation
- Requires attitudinal changes



Distributed Generation Benefits

- Can meet supply requirements
- Can provide security and reliability
- Controllable
- Can assist reduce network connection costs
- Can be part of an energy price risk strategy
- Can be integrated with demand management



Fuel Processing

- Boilers operate best if fuel is homogenous and standard moisture content
- Ensure no rubbish in waste
- Design efficient waste handling into hogger
- Design efficient fuel storage/transport



Combustion

- A good boiler design is hassle free
- Could be fully operated remotely if it wasn't for the fuel
- Good design and well managed fuel quality means no emission problems
- A well designed facility means no dust or mess - can operate in urban areas without being noticed



Electricity generation needs to be part of total integrated energy solutions

